



## Difusor DP3L Aluminio / DP3A Acero

SPRODUCTO + REJILLAS + **DIFUSORES** + FILTROS + DUCTO FLEXIBLE + ACCESORIOS

### Tabla de Selección

	Cuello Velocidad	400	500	600	700	800	900	1000	1200	1400	1600
6"	CFM	80	100	120	135	155	175	195	235	275	315
An .20	Ps	0.008	0.012	0.017	0.021	0.028	0.035	0.043	0.063	0.086	0.112
Ak .78	NC	x	x	x	x	x	x	20	25	30	35
	Tiro	2	3	3	3.5	4	4.5	5	6	7	8
8"	CFM	140	175	210	245	280	315	350	420	490	560
An .35	Ps	0.010	0.015	0.022	0.029	0.038	0.049	0.060	0.086	0.117	0.150
Ak .92	NC	x	x	x	x	20	25	30	35	35	40
	Tiro	3.5	4.5	5.5	6.5	7	8	9	10.5	12.5	14.5
10"	CFM	220	270	325	380	435	490	545	655	765	870
An .54	Ps	0.014	0.021	0.030	0.041	0.054	0.068	0.084	0.122	0.167	0.212
Ak 1.20	NC	x	x	x	20	25	30	35	35	40	45
	Tiro	5.5	7	8.5	10	11	12.5	14	17	19.5	22
12"	CFM	315	390	470	550	630	705	785	940	1100	1255
An .78	Ps	0.015	0.023	0.033	0.045	0.060	0.072	0.094	0.132	0.180	0.230
Ak 1.65	NC	x	x	20	25	30	35	35	40	45	45
	Tiro	6	7.5	9	10.5	12	13.5	15	18	21	24
14"	CFM	430	535	640	750	855	960	1070	1285	1500	1710
An 1.07	Ps	0.023	0.036	0.051	0.071	0.093	0.115	0.140	.205	.277	0.35
Ak 2.06	NC	x	x	20	25	30	35	40	40	45	45
	Tiro	6.5	8	9.5	11.5	13	14.5	16	19	22.5	25

La velocidad terminal de 75 FPM  
AN= Area de cuello en Pies cuadrados

