

Tabla de Selección RF3

LOUVERS + SPIRODUCTO + REJILLAS + DIFUSORES + FILTROS + DUCTO FLEXIBLE + ACCESORIOS

Ancho Nom	Velocidad de salida	400	500	600	700	800	900	1000	1200
Area de sal	Presion Total	0.014	0.02	0.028	0.039	0.052	0.066	0.081	0.113
3"	PCM/pie	66	83	99	116	133	149	166	199
	Tiro repisa	8-9	10-11	14-15	15-17	18-21	20-22	23-24	25-27
	Tiro pared lateral	12-21	15-24	19-27	21-28	23-32	26-34	29-36	30-38
	NC	-	6	10	13	16	18	21	25
4"	PCM/pie	87	109	130	152	174	196	218	261
	Tiro repisa	10-11	12-14	14-18	17-20	19-21	22-24	24-25	26-28
	Tiro pared lateral	14-19	16-23	20-26	22-31	25-33	27-35	30-37	32-40
	NC	-	8	11	14	18	20	22	27
5"	PCM/pie	112	140	168	196	224	252	280	336
	Tiro repisa	11-13	12-15	16-19	19-21	21-33	23-25	25-27	27-29
	Tiro pared lateral	16-20	19-24	21-27	24-33	26-34	28-36	30-38	32-43
	NC	-	8	11	14	18	21	23	28
6"	PCM/pie	133	166	200	233	266	300	333	400
	Tiro repisa	12-14	14-16	17-20	20-22	22-24	24-27	26-29	28-31
	Tiro pared lateral	18-24	20-26	22-29	25-35	26-36	29-38	31-40	33-44
	NC	-	10	13	16	19	22	26	29
8"	PCM/pie	195	244	293	342	390	439	488	585
	Tiro repisa	13-15	16-19	19-21	20-23	23-26	25-29	28-31	30-34
	Tiro pared lateral	16-21	19-24	21-28	23-31	24-33	28-35	30-36	33-39
	NC	-	13	16	19	22	26	29	32
10"	PCM/pie	221	276	331	386	442	497	552	-
	Tiro repisa	14-17	18-20	20-23	22-26	25-29	27-31	28-33	-
	Tiro pared lateral	18-23	20-26	23-30	25-32	27-35	30-36	31-38	-
	NC	-	14	18	21	24	27	30	-
12"	PCM/pie	266	333	400	466	533	600	-	-
	Tiro repisa	15-19	19-22	22-25	24-30	27-33	29-35	-	-
	Tiro pared lateral	20-26	21-28	24-32	28-38	29-39	32-41	-	-
	NC	14	16	19	22	26	29	-	-
14"	PCM/pie	315	394	473	552	630	709	-	-
	Tiro repisa	16-20	20-23	22-26	25-30	28-33	30-35	-	-
	Tiro pared lateral	20-26	22-29	25-33	29-36	30-40	33-41	-	-
	NC	16	18	20	23	28	30	-	-
16"	PCM/pie	390	488	586	683	780	-	-	-
	Tiro repisa	17-21	21-24	23-27	26-31	29-34	-	-	-
	Tiro pared lateral	21-27	23-30	26-34	26-38	31-41	-	-	-
	NC	17	19	22	24	30	-	-	-
18"	PCM/pie	398	498	598	697	-	-	-	-
	Tiro repisa	18-22	22-25	24-28	27-32	-	-	-	-
	Tiro pared lateral	22-28	24-31	27-34	27-39	-	-	-	-
	NC	-	14	18	21	-	-	-	-
20"	PCM/pie	442	552	662	773	-	-	-	-
	Tiro repisa	19-23	23-26	25-29	28-33	-	-	-	-
	Tiro pared lateral	23-29	25-32	28-35	29-40	-	-	-	-
	NC	19	21	24	26	-	-	-	-



Tabla de Selección RF5

LOUVERS + SPIRODUCTO + REJILLAS + DIFUSORES + FILTROS + DUCTO FLEXIBLE + ACCESORIOS

Ancho Nominal	Velocidad de salida	400	500	600	700	800	900	1000	1200
Area de salida	Presion Total	0.009	0.015	0.022	0.029	0.037	0.048	0.06	0.09
3"	PCM/pie	74	93	112	130	150	168	187	224
	Tiro repisa	10-10	12-12	15-17	18-19	22-23	23-24	25-26	27-28
	Tiro pared lateral	13-18	16-22	20-26	22-28	24-32	28-35	32-38	33-40
	NC	-	5	8	12	13	16	18	22
4"	PCM/pie	100	125	150	175	200	225	250	300
	Tiro repisa	12-13	14-15	18-20	22-23	23-24	25-27	27-28	30-32
	Tiro pared lateral	16-20	18-23	21-27	24-32	27-34	30-37	33-40	35-42
	NC	-	6	9	12	15	17	19	23
5"	PCM/pie	125	156	187	218	250	280	312	374
	Tiro repisa	14-15	16-17	20-22	23-24	25-26	27-28	29-31	31-33
	Tiro pared lateral	18-22	20-24	22-28	26-34	29-36	32-39	35-41	37-43
	NC	-	7	10	12	14	18	19	24
6"	PCM/pie	150	187	225	262	300	337	375	450
	Tiro repisa	15-16	18-19	21-23	24-24	26-27	28-30	30-32	32-35
	Tiro pared lateral	20-24	22-27	25-31	27-36	29-38	33-41	36-43	38-45
	NC	-	8	11	13	16	19	21	24
8"	PCM/pie	200	250	300	350	400	450	500	600
	Tiro repisa	17-18	20-22	23-24	24-26	26-30	29-33	31-35	33-37
	Tiro pared lateral	22-28	24-30	26-34	28-38	34-41	36-43	38-45	40-47
	NC	-	7	10	13	16	19	21	24
10"	PCM/pie	250	312	375	437	500	562	625	-
	Tiro repisa	18-20	22-24	25-26	26-29	28-32	30-35	32-37	-
	Tiro pared lateral	23-30	26-32	28-36	30-40	34-43	38-44	40-46	-
	NC	-	12	15	17	20	22	25	-
12"	PCM/pie	300	375	450	525	600	675	-	-
	Tiro repisa	19-23	25-26	26-28	28-31	30-34	32-37	-	-
	Tiro pared lateral	25-32	27-35	29-38	32-42	36-44	40-46	-	-
	NC	12	14	16	19	21	24	-	-

